



INTERIOR TRAINING CHECKLIST

Fabrigard Application:

1. Vehicle interior must be clean and dry prior to application.
2. Fill sure-shot high-pressure sprayer with 16 oz of Fabrigard for standard size vehicle, 32 oz for larger utility vehicles and vans with all cloth interior.
3. Pressurize sure-shot sprayer to 100-125 P.S.I.
4. Always use approved respiration mask when applying Fabrigard.
5. Completely coat, using a criss-cross pattern, vehicle's cloth floors, seats, side panels, and floor mats.
DO NOT SPRAY HEADLINER OR REAR DECK MATERIAL AS THIS MAY CAUSE GLUE TO LOOSEN.
6. If there is any product remaining re-spray heavy traffic areas (drivers floor, seat and floor mats.) Completely use **all** products for proper protection.
7. Using a damp, lint-free cloth wipe off any over spray on plastic or leather as applying.
8. Using the same damp cloth lightly wipe over all cloth areas to break the static bond and "set" Fabrigard product.
9. Let vehicle dry with windows slightly down so not to produce moisture on the interior of the car.
10. Proceed to leather application if need or begin Auto Butler paint application.

Leathergard Application:

1. Leather surfaces must be clean and dry prior to application.
2. Apply Leathergard to the applicator pad, work the cream into it until the applicator is saturated and no cream is visible on the surface of the pad.
3. **BEFORE TREATING VENTILATED LEATHER PANELS, VERIFY THE APPLICATOR PAD IS PROPERLY SATURATED BY TESTING A NON-VENTILATED PANEL.**
This will prevent excess lotion from filling in the holes.
4. Using the applicator pad in a circular, overlapping motion, apply Auto Butler Leathergard to all leather surfaces. Replenish applicator pad, per Step #2, as necessary.
5. After applying Auto Butler Leatherguard, return to your starting point and buff off all treated surfaces with a dry, lint-free towel.
6. Leathergard will dry to a clean non-greasy finish within 10-15 minutes.
7. **DO NOT USE ON SUEDE OR ANILINE TREATED LEATHER PRODUCTS.**
8. Leathergard will be reapplied every 6 months when the customer returns for Paint Protector Applications. It is the customers' responsibility to have their leather reasonably clean before they come in for the re-application or a prep charge may apply.

Note: Leathergard is safe to use on vinyl and plastic interior surfaces.

Dealership Name _____

Employee _____

Auto Butler Trainer _____ Date _____

**This Training Checklist is to assist in personnel training and is not intended to replace common sense.
For Training or Technical Questions call your local Auto Butler Representative or (800) 328-7434**